

DE-COMP COMPOSITES, INC.

HT450-G & HT1000-SS

AUTOCLAVE HOSES

HT450-G

HT450-G is a 3/8" ID, green Kevlar-reinforced silicone rubber hose which incorporates a crush-resistant stainless steel liner to prevent vacuum collapse. The soft silicone exterior is designed to be extremely flexible and to prevent vacuum bag punctures, tool damage, and injury to personnel. Maximum tested continuous use temperature is 450°F/232°C, and maximum autoclave pressure is 250 psi. The HT450-G comes standard with a brass, straight, 1/4" npt male fitting on one end and a right angle on one end and in any length that is required. Straight and 90 degree, 1/4, 3/8, 1/2 inch npt male fittings are available upon request.



HT1000-SS

HT 1000-SS is a 3/8" ID, all stainless steel hose. There is no need for a steel liner with this hose, because the hose itself can take full vacuum. Maximum continuous use temperature is 1000°F/538°C, and maximum autoclave pressure is 1000 psi. The HT1000-SS comes standard with a straight, 1/4" npt male fitting on each end and in any length that is required. Available alternate end fittings are 1/4, 3/8, 1/2 inch female JIC.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.