

# DE-COMP COMPOSITES, INC.

## D250

### BAGGING FILM

D250 is a bagging film that is highly recommended for any applications where high elongation, good tear resistance, and excellent air retention are required. This film is rated for temperatures up to 200°F/93°C.

Due to the fact that D250 has excellent drape and flexibility, and releases easily, this film may be used multiple times.

Typical applications include, but are not limited to, laminates, inflatables, bladders, and thermoformed parts.

### PROPERTIES

Tensile Strength (psi)	9,000
Elongation (%)	400
Tear Resistance (pli)	600
Maximum Use Temperature	200°F/93°C
Minimum Use Temperature	-40°F/-40°C
Thickness (inches)	0.0015
Widths (inches)	55 Sheet 55 V-Fold
Yield (ft <sup>2</sup> /lb)	230
Color	Blue

**Note:** Custom gauges and configurations are available upon request.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.