

# DE-COMP COMPOSITES, INC.

## D350

### BAGGING FILM

D350 is a bagging film developed for high heat resistant applications and is lubricant modified to provide greater surface slip. This film is rated for temperatures up to 340°F/171°C.

Due to the fact that D350 has excellent drape and flexibility, and releases easily, you can expect to use the same piece multiple times.

Typical applications include, but are not limited to, vacuum bagging, inflatables, vacuum forming, laminations, medical products, belting, and protective coverings.

### PROPERTIES

Tensile Strength (psi)	8,700
Elongation (%)	400
Tear Strength (lb/in)	500
Maximum Use Temperature	340E°F/171°C
Thickness (inches)	0.003
Width (inches)	57
Yield (ft <sup>2</sup> /lb)	53
Color	Clear

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.