

DE-COMP COMPOSITES, INC.

D206

General Description-

Laid scrim is a cost-effective reinforcing fabric made by chemically bonding continuous filament yarn in an open mesh construction. It is commonly used to increase tear or puncture resistance, improve dimensional stability, or aid in processing. The utility of scrims can be further enhanced by the use of functional binders for increased chemical, heat or moisture resistance, for proper chemical compatibility with the construction they are reinforcing, or for providing the adhesive properties needed for laminations.

†



Properties

-Excellent dimensional stability

-Tensile strength

-Increase tear resistance

Technical characteristics

Property	
MD Yarn:	None
CD Yarn:	1180d Twaron Black
Pattern:	Off angle laid scrim
Angle of the CD:	75 degrees from CD, 2 yarns per inch
Areal Weight:	20.0 GSM
Other:	KPM3210/P3/59
Carrier Scrim:	1 layer of light polyester carrier scrim

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES. IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.