

# DE-COMP COMPOSITES, INC.

## D227

### General Description-

Laid scrim is a cost-effective reinforcing fabric made by chemically bonding continuous filament yarn in an open mesh construction. It is commonly used to increase tear or puncture resistance, improve dimensional stability, or aid in processing. The utility of scrims can be further enhanced by the use of functional binders for increased chemical, heat or moisture resistance, for proper chemical compatibility with the construction they are reinforcing, or for providing the adhesive properties needed for laminations.



### Properties

-Excellent dimensional stability

-Tensile strength

-Increase tear resistance

### Technical characteristics

Property	
MD Yarn:	None
CD Yarn:	1000d Technora aramid – T240B Black
Pattern:	2 yarns per inch off angle scrim
Angle of the CD:	75 degrees
Areal Weight:	19 gsm
Other:	Composites compatible, slit widths available
Carrier Scrim:	1 layer KPM4412/p3 and 1 layer KPM3210/P3

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES. IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.