

# DE-COMP COMPOSITES, INC.

## TABLE TOP

### POLYURETHANE TABLE TOP

Our polyurethane tops are for use in the composite laminating areas. These table tops are a necessity wherever cutting or handling of composite prepreg takes place. These table tops do not dull the cutting blades nor do they mar or get "tacked" by previous cuts in the same area. Benefits of using the polyurethane tops include savings in the cost of replacing cutters and improved quality of parts.

#### PROPERTIES

Tensile Strength @77°F/25°C (psi)	2,500
Elongation at Break (%)	450
Tear Strength @77°F/25°C (pli)	250
Hardness (Shore A)	88-95
Maximum Width (feet)	5
Maximum Length (feet)	10
Standard Thickness (inches)	1/4, 3/8, & 1/2
Color	Blue, Red, and Green
Note: Other thickness and colors are available upon request	

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.