

DE-COMP COMPOSITES, INC.

D370-S

TEFLON TAPE

D370-S Teflon Tape is a TFE tape without fiberglass and it has stretch.

D370-2S Teflon Tape is used for filler bars and areas where stretch is required.

D370-5S Teflon Tape is used to conform to tool surfaces to offer release and cushioning while hiding tool imperfections.

D370-10S Teflon Tape is used for hot press platens.

PROPERTIES

Maximum Use Temperature	550°F/288°C
Minimum Use Temperature	-100°F/-73°C
Thickness (inches)	0.002, 0.003, 0.005, 0.006, 0.010
Widths (inches)	1 to 20
Length (yards)	18 & 36

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.