

DE-COMP COMPOSITES, INC.

D574-A

POLYESTER FILM WITH ADHESIVE

D574-A is used primarily in metal bond and composite shops to break excessive adhesive and to hold materials in place before and during cure cycles.

PROPERTIES

Elongation (%)	90
Maximum Use Temperature	400°F/204°C
Minimum Use Temperature	-60°F/-51°C
Adhesion	31
Thickness (inches)	0.0025
Standard Roll Size	1" x 72 yd 2" x 72 yd
Color	Blue

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE. HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA, THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.