

# DE-COMP COMPOSITES, INC.

## D318

### Sealant Tape



D318 is designed for use in vacuum bagging that requires elevated temperatures. It will maintain an air tight seal during the cure cycle on composite & metal molds and tools, and then strip clean from the mold during de-bagging. It is formulated without asbestos & solvents. Can also be used as a resin damming tape.

TYPICAL PROPERTIES	
Maximum Use Temperature	250-400°F/204°C
Standard Roll Size (t x w x l)	1/8"x1/2"x25'
Rolls per Case	40
Feet per Case	1,000
Color	Gray
Storage	Keep in cool place at or below 80°F/27°C
Shelf Life	12 months from date of manufacture when stored as specified.

**It is suggested that the material be applied by hand to a clean dry mold or tool at room temperature.**

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Last Modified: 03/20/2015

Section: Sealant Tapes

1519 Eastgate Drive • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750  
E-Mail: [email@decomp.com](mailto:email@decomp.com) • Web Site: [www.decomp.com](http://www.decomp.com)  
Toll Free: 877.609.5088