

# DE-COMP COMPOSITES, INC.

## D5160

### Ultra-High Temp Sealant Tape

D5160 is an advanced process vacuum bag sealant tape that was developed to fulfill the stringent requirements of very high temperature cure requirements. This dark brown colored tape sealant is formulated with a unique base polymer to function throughout a temperature range of 375°F (191°C) to 750°F (399°C). Extended cure cycles of twelve (12) hours or longer are possible.

#### ADVANTAGES:

- Easy to apply by hand (User friendly)
- Ideal for oven or autoclave cure
- 375°F (191°C) to 750°F (399°C) cure cycles
- Strips clean from tool surfaces
- Tenacious adhesion to polyimide films and tool surfaces
- Non-Hazardous and thermally stable

PROPERTIES	
Percent Solids	100%
Consistency Cone Penetration	100-130 (300 Gm LOAD, ASTM D-217)
Application Range	45°F (7°C) to 120°F (49°C)
Service Range	375°F (191°C) to 750°F (399°C)
Standard Roll Size (t x w x l)	3/4" X 1/8" X 30'
Rolls per Case	24
Feet per Case	720
Color	Dark Brown
Storage	Keep in cool dry place. Do not store cartons on end, keep flat.
Shelf Life	One year shelf life from date of manufacture when stored at or below 80°F (27°C).

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Last Modified: 03/27/2007

Section: Sealant Tapes

RR 4 Box 4460 • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750  
E-Mail: [email@decomp.com](mailto:email@decomp.com) • Web Site: [www.decomp.com](http://www.decomp.com)  
Toll Free: 877.609.5088

## D5160 (cont.)

### APPLICATION:

Apply by hand to a clean dry tool or platen with release paper on top. When the sealant tape is in position remove the release paper and lay the film on top. Apply pressure by hand or roller on the sealant tape to obtain maximum adhesion and to ensure positive vacuum. It is recommended to strip below 150°F (66°C) to minimize or reduce the parts from becoming warped. D5160 can be stripped without leaving a residue on metal tool surfaces that have been cooled to room temperature.

### PACKAGING:

D5160 sealant tape is supplied in roll form with a special release paper. Other roll sizes will be considered on request.