## **DE-COMP COMPOSITES, INC.**

## RYMPLECLOTH

## **Wiping Cloth**

This silicone free, biodegradable, purified, crimped wiping cloth is manufactured from 100% woven cotton. It has a unique crimped finish and firmly twisted yarns that provides more surface area for collecting and trapping dirt particles. The soft texture and crimped stretch-like construction provides excellent surface conformity and memory. Our factory controlled purification process produces a highly absorbent wiping cloth which is compatible with cleaning solvents and will result in worry-free wiping and polishing.

PROPERTIES COMPARISON		Boeing Mat'l Spec	Aerospace Mat'l Spec
		BMS15-5D	AMS 3819
	Physical T	ests	
Weight	2.0 oz./sq. yd.	N/A	1.8-6.0
Absorbency	1.4 scc	30 scc max	N/A
Water retention	1950%	N/A	400% min
Lint	4.1 mg/sq. ft.	N/A	10.0 max
Cloth Integrity	No tears	N/A	No tears
7	Chemical t	tests	
Halogen Content	—299 ppm	N/A	N/A
рН	7.2	6.0-7.5	6.0-7.5
IR analysis	No Silicone	No Silicone	No Silicone
I	Extractio	ons	1
Water	0.03%	1.20% max	0.25% max
Acetone	0.18%	1.00% max	N/A
Trichloroethylene	0.16%	0.75%	N/A
Methyl Ethyl Ketone	0.15%	N/A	0.25% max
Dichloromethane	0.13%	N/A	0.25% max
Mil-C-38736	0.05%	N/A	0.25% max
Trichloromethane	0.08%	N/A	0.10% max

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Last Modified: 03/27/2007

Section: Miscellaneous Supplies

RR 4 Box 4460 • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750 E-Mail: email@decomp.com • Web Site: www.decomp.com Toll Free: 877.609.5088

## RYMPLECLOTH (cont.)

	and M ( and M
Composition	100% Purified Cotton
Width (inches)	9-10
Application	Use in cleaning smooth or textured, metallic and non-metallic surfaces where residual surface contamination levels are exceptionally critical. Excellent for applying release agents