

DE-COMP COMPOSITES, INC.

D316SVP Bagging Film

Compatible to the Stretch-Vac 2000 is a pink-tinted, transparent, heat-stabilized blown film produced from a modified polyamide resin which can be used for cures up to 400°F. It is recommended as bagging film for advanced composite fabrication and other high temperature pressure applications where softness, workability and defect-free films are essential.



PROPERTIES	
Tensile Strength (psi)	13,000
Elongation (%)	400%
Tearing Strength (gm/mil)	90
Maximum Use Temperature	400°F/200°C
Minimum Use Temperature	-80°F-61°C
Heat Deflection (66 psi)	412°F/211°C
Melting Point	412°F/211°C
Flammability	Self Extinguishing
Thickness (inches)	0.002
Many Widths available	Sheeting, tubing & V-Fold

SUGGESTED STORAGE METHOD:

All nylon films are known to be hydrophilic. They absorb up to 2.5% of surrounding humidity, therefore, it is recommended that this film be kept in a sealed plastic bag.

NOTE: THE INFORMATION CONTAINED HEREIN IS BELIEVED BY DE-COMP COMPOSITES, INC. TO BE ACCURATE; HOWEVER, NO WARRANTY EXPRESSED OR IMPLIED IS MADE REGARDING THIS DATA. THIS MATERIAL, OR RESULTS THERE FROM WHETHER USED IN ACCORDANCE WITH OUR INSTRUCTIONS OR NOT. THE USER SHALL MAKE HIS/HER OWN TESTS TO DETERMINE SUITABILITY OF THIS MATERIAL FOR HIS/HER PARTICULAR PURPOSES, IN ANY EVENT, DE-COMP'S LIABILITY SHALL BE LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

Page Created: 02/18/2016

Section: Bagging Film

1519 Eastgate Drive • Cleveland, Oklahoma 74020 • Phone: 918.358.5881 • Fax: 918.358.3750
E-Mail: email@decomp.com • Web Site: www.decomp.com
Toll Free: 877.609.5088